

- Multiple SigenStor connection supported for micro-grid system
- Seamless backup, worry-free energy usage for your business
- Generator supported, more abundant backup power
- 350 ms reserve power flow protection of grid & generator
- Uninterrupted power supply through PV+ESS/grid/generator

Sigen Energy Gateway Three Phase

Preliminary

Sigen Gateway	HomeMax TP	C120-6	C300-12	Units
Grid Connection				'
Grid connection type		Three phase		
Nominal AC voltage		380 / 400		V
Nominal AC current	76	182.4	456	Α
Nominal AC power	50 / 52.6	120 / 126.3	300 / 315.9	kW
Nominal AC frequency		50 / 60		Hz
Disruption time of backup switch ¹		0		ms
AC Output to Backup Port				
Nominal AC voltage		380 / 400		V
Nominal AC current	76	182.4	456	А
Nominal AC power	50 / 52.6	120 / 126.3	300 / 315.9	kW
Nominal AC frequency		50 / 60		Hz
Overvoltage category		III		
Inverter Connection				
Number of connection ports	2	6	12	
Nominal AC voltage		380 / 400		V
Max. AC input current	38	45.6	45.6	А
Generator Connection				
Generator output voltage		380 / 400		V
Nominal AC current	76	182.4	456	A
Nominal AC power	50 / 52.7	120 / 126.4	300 / 316	kW
Generator 2-wire start		Supported		
General Data				
Dimensions (W / H / D)	510 / 750 / 179	930 / 1100 / 218	800 / 2300 / 800	mm
Weight	23	74	400	kg
Storage temperature range		-40 ~ 70		°C
Operating temperature range	-30 ~ 55 (Power derating when >35°C in on-grid mode)			°C
Relative humidity range		0% ~ 95%		
Max. operation altitude	4000 (Power derating when >2000m)			m
Cooling	Natural convection			
Ingress protection rating	IP54	IP54	IP20	
Communication	Fast Ethernet , RS485, dry contact			
Installation method	Wall-mounted Wall-mounted Ground-mounted			

This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the backup loads.